

GFK Weighing Scales



The GFK offers all the features needed for weighing, check weighing with LED limit indicators and parts counting application with fully selectable sample or unit weight. Built tough for a variety of industries the GFK can meet the demands of warehouse, production floor or even medical applications.

Check weighing applications are trouble free with amber, green and red indicators to show the operator if the item is under, over or at the preset limits. A stainless steel top pan offers ample weighing surface and a standard pillar allows for easy mounting of the indicator if desired. The GFK includes a RS-232 interface with date and time, bright backlit display with capacity tracker, a built-in rechargeable battery and external power supply.

With over three decades of experience in the production of weighing equipment you can trust Adam for quality products that offer a range of features designed for a many different applications.



AE ADAM[®]
THE RIGHT BALANCE
Speed, Performance, Value

GFK Highlights:

LED indicators for easy recognition of underweight, overweight and acceptable limits makes check weighing applications quick and simple. The colour limits can be programmed to turn on together or in sequence for a more detailed indication.

Bright backlit display with capacity tracker is easy to read. The tracker shows the operator where they are in the weighing range, when using the tare function, to help prevent the user from exceeding the scales capacity.

Full numeric keypad allows for preset tare functions and freely selectable sample size when in counting mode. The keypad and functions can be locked out by a supervisor if needed to stop settings from being changed.

The most flexible platform scale to meet today's demanding applications

Features


- Full tare range
- Easily accessible internal rechargeable battery
- Large backlit LCD display with capacity tracker
- Battery operation with auto-off to save battery life
- Parts counting with freely selectable sample sizes
- Check weighing LED lights to show acceptable limits
- Automatic accumulation
- Bi-directional RS-232 output for connection to computers and printers
- Multi-language print-outs.
- OIML approved (M version only)

Applications

- Weighing
- Parts counting
- Percentage weighing
- Dynamic/Animal weighing
- Check weighing
- Check counting



Bright display




Stainless steel (grade 304) top pan



LED Lights for check weighing

Technical Specifications

| Model | GFK 75 | GFK 150 | GFK 300 | GFK 600 | GFK 75H | GFK 150H | GFK 60M | GFK 150M | GFK 300M |
|-----------------------|---|---------|---------|-------------------|-------------------|----------|---|----------|----------|
| Capacity | 75kg | 150kg | 300kg | 600kg | 75kg | 150kg | 60kg | 150kg | 300kg |
| Readability | 5g | 10g | 20g | 50g | 1g | 2g | 20g | 50g | 100g |
| Repeatability (S.D.) | 5g | 10g | 20g | 50g | 2g | 4g | 1d | 1d | 1d |
| Linearity (+/-) | 10g | 20g | 40g | 100g | 3g | 6g | 2d | 2d | 2d |
| Pan Size | 400 x 500mm | | | 800 X 600mm | 400 x 500mm | | | | |
| Weighing Units | Gram (g) , Kilgrams (kg) | | | | | | | | |
| Stabilisation Time | 2-3 secs | | | | | | | | |
| Calibration | Automatic External | | | | | | | | |
| Display | Backlit Green display with 25mm digits and capacity tracker | | | | | | | | |
| Power Supply | Internal 220v transformer / 6v 4aH battery | | | | | | | | |
| Operating Temperature | -10°C - 40°C | | | | | | | | |
| Housing | ABS Plastic Indicator and Stainless steel pan | | | | | | | | |
| Approvals | Non approved | | | | | | OIML Approved  | | |
| Overall Dimensions | 400 x 620 x 860mm | | | 600 x 950 x 860mm | 400 x 620 x 860mm | | | | |
| Net Weight | 16kg | | | 50kg | 16kg | | | | |

Accessories

- Item No. 8023 - Adam Printer
- Item No. 9192 - Replacement Paper (5 pack)
- Item No. 9665 - In-use cover