AELP Pallet Beams & AE 402 Indicator



The AELP series of pallet beams are ideal for pallet weighing and oversized weighing applications. The Adam AELP is easy-to-use and move, with built in wheels and handles for mobility. The AELP comes standard with the AE402 indicator that features a bright green LCD display that can be read in difficult lighting conditions. The AELP offers fast, precise mobile weighing along with many other features. Ŵ

HEADAM®

THE RIGHT BALANCE

Speed, Performance, Value

With over 35 years of experience in the production of weighing instruments you can trust Adam for quality products that offer a range of features designed for a variety of applications.







AELP

AELP pallet beams feature a low profile design for easy loading and unloading. The Adam AELP is easy-to-use and move, with built in wheels and handles for mobility.

The AELP offers fast, precise mobile weighing along with many other features.

GK Indicator

With a number of weighing modes and units the GK indicators can be adapted to a wider range of applications. A large backlit display is easy to read with a capacity tracker to help protect from overloading and the colored LED indicators are ideal for check weighing applications to measure underweight, overweight and acceptable limits. With standard RS-232 interface for computers and printers, rechargeable battery and AC adapter powered, and full numerical keypad, the GK offers the most value for an indicator.

AE 402 Indicator

The AE 402 is a multi-purpose weighing indicator that can be used for a wide range of applications. With a large easy-to-read backlit LCD display this indicator provides faster readings. The AE 402 offers digital filters, memory accumulation, tare, display hold, RS-232 interface, plus an internal rechargeable battery and an AC adapter included.

Features

- Lightweight with handles for portability
- Precision load cells for accurate weighing results
- Low profile beams for easy weighing of all kinds of pallets
- 2 beams per set
- Comes with with AE402 indicator
- Large clear display
- Selectable digital filtering
- Uni-directional RS232 interface.
- Rechargeable battery / mains adaptor supplied as standard.

Features

- Full tare range
- Accessible internal rechargeable battery
 Large backlit LCD display with capacity
- tracker
 Battery operation with auto-off to save
- battery life
 Check weighing LED lights to show acceptable limits
- Bi-directional RS-232 output for connection to computers and printers

Features

- Hold Function
- Full range tare
- Backlit LCD display
 - Wall mount bracket Supports upto four 350 ohm loadcells
- Bi-directional RS-232 interface

Technical Specifications

AELP Pallet Beams							
Model	Maximum Scale Capacity (kg)	Beam Size (w x d x h each)	Net Weight (lb/kg)	Cable	Construction		
AELP 1000	1000kg	- 1200 x 120 x 85mm	50kg	3m long	Mild steel beams		
AELP 2000	2000kg						

GK Indicators

Model	Readability	Loadcells	Zero input range	Signal Range	Weighing Units	Readability
GK	Up to 1:30,000	Up to 4 x 350ohm loadcells	0 - 10mV	0 - 40mV	g, kg, lb, oz, lb:oz	Selectable

AE 402 Indicators

Model	Readability	Loadcells	Zero input range	Signal Range	Weighing Units	Readability
AE 402	Up to 1:30,000	Up to 4 , 350 ohm loadcells – Minimum 87ohms, maximum 1120ohms	0- 10mv	0+40mv	kg / lb / oz	Selectable

Accessories

- Item No. 8023 Adam Printer
- Item No. 9665 In-Use Cover for GK
- Item No. 9192 Thermal replacement paper (5-pack)



www.adamequipment.com

Adam Equipment follows a policy of continuous improvement and reserves the right to change specification and pricing without notice. Adam Equipment's standard terms and conditions of sale apply. Errors and Omissions excepted. ©Adam Equipment 2009.